

Ultrasonic Thickness Gauge

Whatever the application, Tritex have a gauge suited specifically for it. The rugged designs not only look good but are also durable. All probes have IPR (Intelligent Probe Recognition), which automatically adjusts settings in the gauge at the same time as transmitting recognition data - the result is a perfectly matched probe and gauge for enhanced performance. That's not all; the AMVS (Automatic Measurement Verification System) ensures only true measurements are displayed, even on the most heavily corroded metals.

Housed in purpose designed cases and incorporating Triple Echo to completely ignore coatings, Tritex Multigauges are the choice for the future...

Multigauche 5600

The Multigauche 5600 is a simple, robust ultrasonic thickness gauge designed for most common thickness gauging applications. The easy to use keypad allows operator interface whilst the bright LCD display can be used in all light conditions. The moulded soft rubber surround feels comfortable, looks good and provides extra protection against knocks and scrapes.



simple . accurate . robust



Typical Applications


- | | |
|-----------------|--------------------|
| Shipping | Pipelines |
| Bridges | Road Tankers |
| Pilings | Offshore Platforms |
| Storage Tanks | Lighting Columns |
| Industry | Phone Masts |
| Quality Control | Lock Gates |
| Leisure Craft | Barges |

About Triple Echo

All Ultrasonic Thickness Gauges should be calibrated to the velocity of sound of the material being measured. Coatings have a different velocity of sound than metal and it is important they are not included in the measurement. Triple Echo ensures all coatings are completely eliminated from the measurement.

How it works:

A transmitted ultrasound pulse travels through both the coating and the metal and reflects from the back wall. The returned echo then reverberates within the metal, with only a small portion of the echo travelling back through the coating each time. The timing between the small echoes gives us the timing of the echoes within the metal, which relate to the metal thickness. The returned echoes need not be consecutive as the gauge will interpret them automatically and calculate the thickness. A minimum of three echoes are checked each time. This is referred to as the Automatic Measurement Verification System (AMVS).



Specification

Sound Velocity Range	From 1000 m/s to 8000 m/s (0.0394 in/μs to 0.3150 in/μs)		
Single Crystal Soft Faced Probe Options	2.25 MHz	3.5 MHz	5 MHz
Probe Measurement Range	3 - 250 mm (0.120" to 10")	2 - 150 mm (0.080" to 6")	1 - 50 mm (0.040" to 2")
Probe Sizes	13 mm (0.5") & 19 mm (0.75")	13 mm (0.5")	6 mm (0.25") & 13 mm (0.5")
Resolution	0.1 mm (0.005") or 0.05 mm (0.002")		
Accuracy	± 0.1 mm (0.005") or ± 0.05 mm (0.002")		
Display	Multi character LCD with white back light		
Batteries	3 x disposable AA alkaline batteries or rechargeable NiMH / NiCD		
Battery Life	20 Hours continuous use using alkaline batteries		
Gauge Dimensions	147 mm x 90 mm x 28 mm (5.75" X 3.5" X 1")		
Gauge Weight	330 g (11.6 ounces) including batteries		
Environmental	Case rated to IP65. RoHS and WEEE compliant		
Operating Temperature	-10°C to +50°C (14°F to 122°F)		
Storage Temperature	-10°C to +60°C (14°F to 140°F)		

The Tritex Multigauge 5600 has been manufactured to comply with British Standard BS EN 15317:2007, which covers the characterisation and verification of ultrasonic thickness measuring equipment.



Contact

Tritex NDT Ltd
Unit 10
Mellstock Business Park
Higher Bockhampton
Dorchester, Dorset
United Kingdom
DT2 8QJ

t: +44 (0) 1305 257160
f: +44 (0) 1305 259573
e: sales@tritexndt.com
w: www.tritexndt.com

simple . accurate . robust

