

Flow Measurement

SITRANS FC (Coriolis)

Sensors and Flowmeter systems

SITRANS FC330 flowmeter system

Overview



The complete flowmeter system SITRANS FC330 can be ordered for standard, hygienic or NAMUR service. The flowmeter is based on the latest developments within digital signal processing technology – engineered for high measuring performance:

- Fast response to rapid changes in flow
- Fast dosing applications
- High immunity against process noise
- High turndown ratio of flowrates
- Suitable for liquid and gas service
- Easy to install, commission and maintain

With all global marine approvals the FC330 is ideal for integration in ship fuel efficiency and environmental measurement systems as well as bunkering solutions.

FC330 is available with current output HART 7.5, Modbus RS 485 RTU, PROFIBUS DP or PROFIBUS PA as standard on Channel 1. Additional functions can be freely configured for analog, pulse, frequency, relay or status output or binary input.

The transmitter comes with a user-configurable graphical display and SensorFlash, a micro SD card for configuration backup, firmware update and data storage.

The SITRANS FC330 flowmeter system consists of a SITRANS FCS300 sensor and a SITRANS FCT030 transmitter.

Benefits

- It is compact and light, fitting neatly into dense piping arrangements
- Easy maintenance because modules can be exchanged rapidly
- Effective separation of measurement from plant vibration
- Highly secure operation in safety critical applications
- Non-volatile memory of all setup and operation data
- Reliable measurements due to high signal to noise ratio
- Secure, digital transfer of measurement data from the sensor
- Short overall length; easy drop-in replacement into most existing installations

Technical specifications

Sizes	DN 15 (½") DN 25 (1") DN 50 (2") DN 80 (3") DN 100 (4") DN 150 (6")	Process connections	EN 1092-1 B1, EN 1092-1 B2, EN 1092-1 D, ANSI/ASME B16.5, JIS B 2220
Accuracy	± 0.10 % or 0.20 % for liquids additional ± 0.40 for gases	• Pipe threads	ASME B1.20 (NPT) female pipe thread, ISO 228-1 G female pipe thread (BSPP)
Repeatability	± 0.05 %	• Hygienic threads	DIN 11851, SMS 1145
Flow range (liquids) (water @ 1 bar pressure loss) (Q_{nom})	4 500 kg/h (163.3 lb/min) 20 500 kg/h (753.2 lb/min) 49 000 kg/h (1 800 lb/min) 122 000 kg/h (4 483 lb/min) 273 000 kg (10 031 lb/min) 459 200 kg/h (16 873 lb/min)	• Hygienic clamps	DIN 32676 (ISO) Row A
Architecture	Compact or remote configuration	Approvals	
Display	Full graphical display, 240 × 160 pixels with selection of 6 languages	• Hazardous area (zone 1)	ATEX, IECEx, EAC Ex, CSA, cCSAus, NEPSI, EAC No dust approval
Power supply	20 ... 90 V DC ± 10 %; 100 ... 240 V AC ± 10 %, 47 ... 63 Hz ± 10 %	• Pressure equipment	PED, CRN
Material		• Hygienic	EHEDG (DN 25 ... DN 80) (in preparation)
• Sensor - Wetted parts - Enclosure	316L stainless steel or nickel alloy C4 304 stainless steel	• Marine (in preparation for FC330 compact)	Germanischer Lloyd/det Norske Veritas, Bureau Veritas, Lloyds of London, American Bureau of Shipping, RINA (Italy)
• Transmitter	Aluminum with corrosion-resistant coating class C4	NAMUR	NAMUR-compliant (e.g. NE 21, NE 41, NE 107 and NE 132)
Enclosure rating	IP67 ¹⁾	I/O	Up to 4 channels combining analog, relay or digital outputs and binary input
Pressure ratings		Communication	HART PROFIBUS PA PROFIBUS DP Modbus RTU (RS 485)
• Measuring tubes - 316L - Nickel alloy C4	100 bar (1 450 psi) 100 bar (1 450 psi)	EMC performance	EN 55011/CISPR-11 (Class A)
• Sensor enclosure	No pressure containment	Emission	EN/IEC 61326-1 (Industry)
Temperature ratings		Mechanical load	18 ... 400 Hz random The flow meter will mechanically tolerate 3.17 g RMS in all directions. Flow accuracy cannot be guaranteed under all conditions.
• Process medium • Ambient • Display	-50 ... +205 °C (-58 ... +400 °F) -40 ... +60 °C (-40 ... +140 °F) -20 ... +60 °C (-4 ... +140 °F)	1) If operating outdoors, avoid direct sunlight, particularly in warm climatic regions.	

Flow Measurement

SITRANS FC (Coriolis)

Sensors and Flowmeter systems

SITRANS FC330 flowmeter system

Selection and ordering data

Article No.

Article No.

SITRANS FC330 digital coriolis flowmeter with SITRANS FCS300 standard flow sensor compact or remote mounting with FCT030 transmitter

↗ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.

Sensor size, connector size

DN 15, DN 10 (½", 3/8")

7ME4633-

Ord. code

DN 15, DN 15 (½", ½")

3 F

DN 15, DN 20 (½", ¾")

3 G

DN 25, DN 20 (1", ¾")

3 H

DN 25, DN 25 (1", 1")

3 K

DN 25, DN 40 (1", 1½")

3 L

DN 50, DN 40 (2", 1½")

3 N

DN 50, DN 50 (2", 2")

4 B

DN 50, DN 65 (2", 2½")

4 C

DN 80, DN 65 (3", 2½")

4 D

DN 80, DN 80 (3", 3")

4 J

DN 80, DN 100 (3", 4")

4 K

DN 100, DN 80 (4", 3")

4 L

DN 100, DN 100 (4", 4")

5 M

DN 100, DN 150 (4", 6")

5 N

DN 150, DN 100 (6", 4")

5 Q

DN 150, DN 150 (6", 6")

6 D

DN 150, DN 200 (6", 8")

6 F

Process connection

6 H

EN 1092-1 B1, PN 16

A 0

EN 1092-1 B1, PN 40

A 1

EN 1092-1 B2, PN 63

A 2

EN 1092-1 B2, PN 100

A 3

EN 1092-1 D, PN 40

A 5

ASME B16.5 RF, class 150

D 1

ASME B16.5 RF, Class 300

D 2

ASME B16.5 RF, Class 600

D 3

ASME B16.5 RF, Class 900
(p- and t-rating as Class 600)

D 4

ASME B16.5 RF, Class 1500
(p- and t-rating as Class 600)

D 5

ISO 228-1G female pipe thread

E 1

ASME B1.20.1 NPT female pipe thread

E 3

DIN 11851 hygienic screwed

F 1

DIN 32676 hygienic clamp (ISO) Row A

G 2

SMS 1145 hygienic screwed

K 1

JIS B2220/10K

L 2

JIS B2220/20K

L 4

EN 1092-1, PN 16, NAMUR length

N 1

EN 1092-1, PN 40, NAMUR length

N 2

Wetted parts material

AISI 316L/1.4435/1.4404

1

AISI 316L/1.4435/1.4404 (polished)

2

Nickel alloy C4

3

SITRANS FC330 digital coriolis flowmeter with SITRANS FCS300 standard flow sensor compact or remote mounting with FCT030 transmitter

Calibration/Accuracy class

0.2 % flow, 10 kg/m³ density

0

0.1 % flow, 2 kg/m³ density

1

0.1 % Standard fraction (with density 2 kg/m³)

8

0.1 % Customer selected fraction

9

Mounting style, transmitter housing and material

None (replacement sensor)

A

Compact, IP67 fieldmount, aluminum

D

Remote, IP67 fieldmount, aluminum, M12

G

Remote, IP67 fieldmount, aluminum, T/Box

K

Remote, IP67, wall mount, aluminum (in preparation)

U

Ex approval (depending on variant)

Non-Ex

A

ATEX (zone 1)

C

IECEx (zone 1)

F

US (cCSAus), Div 1

L

Canada (cCSAus), zone 1

M

NEPSI

N

INMETRO (in preparation)

P

KCC (in preparation)

Q

EAC

U

Local User Interface

None (replacement sensor, DSL only)

0

Blind

1

Graphical, 240 × 160 pxl

3

Selection and ordering data

Order code

Further designs

Please add "-Z" to Article No. and specify Order code(s).

Cable glands

None (replacement sensor)

A00

Metric, no glands

A01

Metric, nylon, limited to -20 °C/-4 °F

A02

Metric, brass/Ni plated

A05

Metric, stainless steel

A06

NPT, no glands

A11

NPT, nylon, limited to -20 °C/-4 °F

A12

NPT, brass/Ni plated

A15

NPT, stainless steel

A16

Metric thread with M12 socket fitted

A20

Software functions and CT approvals

None (replacement sensor)

B10

Standard

B11

Selection and ordering data	Order code	Order code
Further designs Please add "-Z" to Article No. and specify Order code(s).		Add-on options and accessories Please add "-Z" to Article No. and specify Order code(s).
I/O configuration Ch1		Customer selected calibration
No output channel	E00	DN 15 ... 50: Multi-point (5 flows × 1 pass) Flow 10 ... 100 % of Q_{norm} D60
4 ... 20 mA HART Active/Passive (non-Ex)	E02	DN 15 ... 50: Multi-point (10 flows × 1 pass) Flow 10 ... 100 % of Q_{norm} D61
Ca 4 ... 20 mA HART active (Ex)	E06	DN 80: Multi-point (5 flows × 1 pass) Flow 10 ... 100 % of Q_{norm} D62
Ca 4 ... 20 mA HART passive (Ex)	E07	DN 80: Multi-point (10 flows × 1 pass) Flow 10 ... 100 % of Q_{norm} D63
PROFIBUS PA	E10	DN 100: Multi-point (5 flows × 1 pass) Flow 10 ... 100 % of Q_{norm} D64
PROFIBUS DP (non-Ex)	E11	DN 100: Multi-point (10 flows × 1 pass) Flow 10 ... 100 % of Q_{norm} D65
Modbus RTU RS 485	E14	DN 150: Multi-point (5 flows × 1 pass) Flow 10 ... 100 % of Q_{norm} D66
I/O configuration Ch2, Ch3 and Ch4		DN 150: Multi-point (8 flows × 1 pass) Flow 10 ... 100 % of Q_{norm} D67
None	F00	Cable
• Non Ex: Sig O, None, None	F01	None L50
• Non Ex: Sig O, Sig I/O, None	F02	5 m (16.4 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted L51
• Non Ex: Sig O, Sig I/O, Sig I/O	F03	5 m (16.4 ft), sensor cable, 4 wire, without plugs for terminal connection L52
• Non Ex: Sig O, Sig I/O, R	F04	10 m (32.8 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted L55
• Non Ex: Sig O, R, R	F05	10 m (32.8 ft), sensor cable, 4 wire, without plugs for terminal connection L56
• Non Ex: Sig O, R, None	F06	25 m (82 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted L59
• Ex: pSig O, None, None	F11	25 m (82 ft), sensor cable, 4 wire, without plugs for terminal connection L60
• Ex: pSig O, pSig I/O, None	F12	50 m (164 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted L63
• Ex: pSig O, pSig I/O, pSig I/O	F13	50 m (164 ft), sensor cable, 4 wire, without plugs for terminal connection L64
• Ex: pSig O, pSig I/O, R	F14	75 m (246 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted L67
• Ex: pSig O, R, R	F15	75 m (246 ft), sensor cable, 4 wire, without plugs for terminal connection L68
• Ex: pSig O, R, None	F16	
• Ex: aSig O, None, None	F21	
• Ex: aSig O, aSig I/O, None	F22	
• Ex: aSig O, aSig I/O, aSig I/O	F23	
• Ex: aSig O, aSig I/O, R	F24	
• Ex: aSig O, R, R	F25	
• Ex: aSig O, R, None	F26	
Notes on I/O configurations:		
a or p suffix: The I/O module is selected at ordering with either active or passive function.		
Signal: The output can be selected for Current (0 or 4 to 20 mA), frequency or pulse function in the menu.		
I: Discrete status input to the flowmeter. Functions are selected in the menu including 'Freeze output', 'Reset totalizer' (only CH3&4).		
R: Relay output for discrete status reporting. Function is selected in the menu, including 'Error', 'High flow warning'.		
The MLFB structure for FC330 systems must be filled to this level , including "-Z" options A.., B.., E.. and F.		
Add-on options and accessories Please add "-Z" to Article No. and specify Order code(s).		Sensor options FCS300 marine approval (in preparation) S22
Certificates		SD-Card accessibility via USB (not allowed in USA by Patent)
Certificate EN 10204-2.2 confirmation of pressure containing material	C01	Mass storage enabled S30
Certificate EN 10204-3.1 material (wetted parts)	C02	
Material certificate EN 10204-3.2 with inspection	C03	
Certificate NACE MR0175-2009 + MR0103-2012	C04	
Certificate EN 10204-2.1 Declaration of compliance with the order	C05	
Insp. Certificate EN 10204-3.1 for visual, dimensional and functional test	C06	
Certificate EN 10204-3.1 PMI Positive material ident. of pressure-cont./wetted parts (confirmation only)	C07	
Certificate EN 10204-3.1 P-test Pressure-test acc. AD2000	C08	
Test pack (pressure test, non-destructive welding test, welder & welding procedure certificate)	C09	
Certificate EN10204-3.1 welding X-ray / Dye-penetration test of weldings (pressure cont.)	C10	
Certificate EN10204-2.1 Declaration of accuracy	C11	
Certificate EN10204-3.1 PMI Positive material ident. of pressure-cont./wetted parts (including heat analysis)	C12	
Operating instructions for SITRANS FC330		
Description		Article No.
English		
• for firmware V 4.0 and onwards		A5E44030648
German		
• for firmware V 4.0 and onwards		TBD
All literature is available to download for free, in a range of languages, at		
www.siemens.com/processinstrumentation/documentation		